

B-06/07



WHITE/GREY CEMENT

Suitable for masonry plastering, floor repair, wall scaling, etc.



SURFACES

Cement, concrete, bricks.
Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

CHARACTERISTICS

- Available in white and grey.
- Adheres to porous stone and cement surfaces.
- Storage: 12 months in its original packaging and protected from moisture.

IDEAL FOR

- Mortar production.
- Tile grouting.
- Mortars or adhesive cement additive.



Pallet of 35 boxes
of 4 x 5 Kg



Pallet of 42 boxes
of 12 x 1,5 Kg



Mixing water ratio
0,35 litres of water per kg of plaster



Performance
Variable according



13.0 - 14.0



Maximum thickness per layer
Unlimited



Maximum granulometry
300 microns



Fire classification
A1



Use time
> 45 mins.



Density
1,10 ± 0,07



Resistance to compression
42.5 MPa



BAIXENS ESPAÑA
POL. IND. MONCARRA, S/N
46230 ALGINET (VALENCIA)
T.: 961.750.834
F.: 961.752.471

BAIXENS FRANCE
14, RUE DU PONT NEUF
75001 PARIS (FRANCE)
T.: 0.800.90.14.37
F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA
VIA PIETRO NENNI, 36
46019 CICOGNARA - MANTOVA (ITALY)
T.: 0375/88181/790016 F.: 0375/88831
www.bulova-pennelli.com

BAIXENS PORTUGAL / ARGATINTAS
AVENIDA PORTAS DO MINHO, Nº 711
4760 - 706 RIBEIRÃO,
V.N. FAMILICÃO
T.: 252 910 030 | www.argatintas.pt

BO6NFMPA20 / BO7NFMPA20