

B-10

BRICO®

CRACK COVERING PUTTY

Product suitable for smoothing and covering cracks and non-movement fissure.



CLASSIFICATION ACCORDING TO
REGULATION EN 16566

G3S2V3W2A0C0R0

USES

Gypsum, plaster, cement, stone, brick and non-elastic synthetic paint.
Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Normal setting.
- Easy to apply, smooth and sand.
- Thin layer applicable.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Smoothing of walls with flaws (scratches, lines, dents...).
- Fill in of defects in wood.



Pallet of 66 sacks
of 15 Kg



Pallet of 35 cases
of 4 x 5 Kg



Pallet of 42 cases
of 12 x 1 Kg



Water for mixing

0,38-0,43 litres of water per kg of powder



Performance

0,6 m²/kg



6.0 - 7.0



Maximum thickness per layer

1 mm



Adherence

> 7 Kg/cm² on cement and paint



Fire classification

A1



Useful life

7 - 8 hrs.



Drying in 1 mm thickness

Concrete and paint: 4 – 6 hrs. approx
Plaster: 3 – 4 hrs. approx



Maximum granulometry

300 microns