

B-11

BRICO®

## FILLER PUTTY

Product suitable for filling in of non-structural holes and cracks in gypsum and cement walls.



CLASSIFICATION ACCORDING TO  
REGULATION EN 16566

**G3S2V3W2A0C0R0**

### USES

Gypsum, cement, non-elastic synthetic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

### FEATURES

- Easy to sand.
- Applicable in thin or thick layer.
- Fast setting.
- Easy to apply
- Storage: 6 months inside its original packing and kept free from damp and humidity.

### IDEAL FOR

- Filling in of non-structural holes and cracks.



Pallet of 66 sacks  
of 15 Kg



Pallet of 35 cases  
of 4 x 5 Kg



Pallet of 42 cases  
of 12 x 1 Kg



#### Water for mixing

0,45-0,50 litres of water per kg of powder



#### Performance

0,66 m<sup>2</sup>/kg



6.0 - 7.0



#### Maximum thickness per layer

10 mm. for plastering  
Unlimited for covering



#### Adherence

> 4 Kg/cm<sup>2</sup> on cement  
> 3 Kg/cm<sup>2</sup> on paint



#### Fire classification

A1



#### Useful life

30' - 60'



#### Drying in 1 mm thickness

Concrete and paint: 4 - 6 hrs. approx  
Plaster: 3 - 4 hrs. approx



#### Maximum granulometry

200 microns