

B-12

BRICO®

EXTERIOR PUTTY

Product suitable for smoothing and covering of exterior substrates in thin or medium layer.



USES

Cement, concrete, brick or stone walls.
Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Standard setting
- White colour.
- Easy to apply
- Applicable in thin or medium layer (4mm/layer).
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Filling in of non-movement cracks and of non-structural features.
- Smoothing and plastering of exterior walls.
- Recoating of fissures or micro-fissures.



CLASSIFICATION ACCORDING TO
REGULATION EN 16566

G3S2V2W2A0C0R0



Pallet of 66 sacks
of 15 Kg



Pallet of 35 cases
of 4 x 5 Kg



Pallet of 42 cases
of 12 x 1,5 Kg



Water for mixing

0,35-0,40 litres of water per kg of powder



Performance

0,68 m²/kg



12.0 - 13.0



Maximum thickness per layer

4 mm. for plastering
Unlimited for covering



Adherence

> 7 Kg/cm² on cement



Fire classification

A1 and A1_{FL}



Useful life

2 Hrs. 30' – 3 Hrs. 30'



Drying in 1 mm thickness

Concrete: 3 – 4 hrs.



Maximum granulometry

300 microns