

B-13

BRICO®

## PUTTY EVERYTHING

Product suitable for pasting tiles, repairing façades, exterior walls and renovating interior patios.



CLASSIFICATION ACCORDING TO  
REGULATION EN 16566

**G3S3V3W1A0C0R0**

### USES

Gypsum, plaster, cement, concrete, brick walls, stone, synthetic paint, tiles and low absorption bases

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

### FEATURES

- Fast setting
- Quick dry.
- Applicable in thin or thick layer.
- Easy to apply
- Good adherence.
- Hard finish.
- Storage: 6 months inside its original packing and kept free from damp and humidity.

### IDEAL FOR

- Filling in plastering, repairs and renovation of façades.
- Filling in of non-structural cracks and façade cavities.
- Plastering and renovating of bathrooms, kitchens and covering of old tile surfaces inclusive.



Pallet of 35 cases  
of 4 x 5 Kg



Pallet of 42 cases  
of 12 x 1 Kg



#### Water for mixing

0,35-0,40 litres of water per kg of powder



#### Performance

0,65 m<sup>2</sup>/kg



10.0 - 11.0



#### Maximum thickness per layer

4 mm. for plastering  
Unlimited for covering



#### Adherence

> 15 Kg/cm<sup>2</sup> on cement



#### Fire classification

A2 - s1 - d0



#### Useful life

20' - 40'



#### Drying in 1 mm thickness

Concrete: 3 - 4 hrs.



#### Maximum granulometry

300 microns