

B-14

BRICO®

SWIMMING POOL REPAIRER

Product suitable for repairing swimming pool joints, repairing of dents and also for pasting loose pieces of tile.



OUTDOOR



CLASSIFICATION ACCORDING TO
REGULATION EN 16566

G3S3V3W1A0C0R0

USES

Gypsum, plaster, cement, concrete, brick walls, stone, synthetic paint, tiles and low absorption bases

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Fast setting
- Quick dry.
- Applicable in thin or thick layer.
- Easy to apply
- Good adherence.
- Very hard finish.
- Storage: 6 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Levelling of walls and renovating ornamental edges of swimming pools or fountains.
- Fixation of railings or stairs.
- Filling in of non-structural cracks and façade cavities.
- Repairing of swimming pool tiles



Pallet of 35 cases
of 4 x 5 Kg



Pallet of 42 cases
of 12 x 1 Kg



Water for mixing

0,35-0,40 litres of water per kg of powder



Performance

0,70 m²/kg



10.0 - 11.0



Maximum thickness per layer

10 mm. for plastering
Unlimited for covering



Adherence

> 15 Kg/cm² on cement



Fire classification

A2 - s1 - d0



Useful life

20' - 40'



Drying in 1 mm thickness

Concrete: 3 - 4 hrs.



Maximum granulometry

300 microns