


B-17

BRICO®

UNIVERSAL PUTTY

Product suitable for repairing and fixation of chimneys/fireplaces, ovens, etc.



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY I1, HIGH PERFORMANCE WATER-BASED COATINGS OF ONE COMPONENT

Limit: 140 g/l COV (2007); 140 g/l COV (2010)
This product contains 5,85 g/l COV max.

USES

Gypsum, plaster, cement, synthetic paint, stoneware tiles.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Extra white.
- Easy to apply and excellent workability.
- Slightly textured product.
- Easy to apply, smooth and sand.
- Strong adherence.
- Thin layer applicable.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Plastering and renovating of tiles.
- Thin layer smoothing of exterior substrates.



Pallet of 120 cases
of 12 x 200 g



Preparation

Ready to use



Performance

0,70 m²/kg



7.0 - 8.0



Maximum thickness per layer

1 mm.



Adherence

> 10 Kg/cm² on cement and paint



Fire classification

A1 - s1 - d0



Useful life

Unlimited



Drying time in 1mm thickness

Plaster: 3 - 4 hrs. approx
Concrete: 5 - 6 hrs
Tiles: 6 - 7 hrs



Maximum granulometry

200 microns