

B-18

BRICO®

COVER-CRACK PUTTY

Product suitable for filling in and covering small holes, lines, dents, fissures, micro-fissures and non-movement cracks.



INDOOR



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY i1, HIGH PERFORMANCE WATER-BASED COATINGS OF ONE COMPONENT

Limit: 140 g/l COV (2007); 140 g/l COV (2010)

This product contains 6,90 g/l COV max.

USES

Gypsum, plaster, cement, non-elastic synthetic paint, synthetic stucco, fiberglass fabric. Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Excellent workability.
- Easy to smooth and sand.
- Non-drip.
- Excellent covering power.
- Can be covered by all types of standard paints once completely dry
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Repairing of lines, dents and micro-fissures.



Pallet of 120 cases
of 12 x 200 g



Preparation

Ready to use



Performance

0,55 m²/kg



9.0 - 10.0



Maximum thickness per layer

1 mm.



Adherence

> 8 Kg/cm² on concrete and paint



Fire classification

A1 - s1 - d0



Useful life

Unlimited



Drying time in 1mm thickness

Cement and paint: 6 - 7 hrs



Maximum granulometry

< 50 microns