B-22





UNIVERSAL ADHESIVE

Product suitable for gluing and pasting any type of material.









INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY i1, HIGH PERFORMANCE WATER-BASED COATINGS OF ONE COMPONENT

Limit: 140 g/l COV (2007); 140 g/l COV (2010)

This product contains 4,94 g/l COV max.

USES

Moulds, rosettes, ceiling lamps, skirting boards, frames, gypsum, brick, wood, plastic, ceramics, cork and polystyrene.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Solid and permanent fastening.
- Excellent adherence and elasticity.
- Easy to apply.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

 Gluing wood, parquet, polystyrene, earthenware, ceramics and any type of product of absorbent surface.





Pallet of 120 cases of 12 x 200 g



PreparationReady to use



Performance 0,75 m²/Kg



7.0 - 8.0



Maximum thickness per layer 2 mm.



Adherence > 13 Kg/cm² on cement



Fire classification E - d0



Useful life
Unlimited



Dryng time in 1mm thickness



Maximum granulometry 200 microns