

B-24

BRICO®

## TILE JOINTS

Product suitable for filling in, renovating, waterproofing and sealing tile joints up to 1mm.



## INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY i1, HIGH PERFORMANCE WATER-BASED COATINGS OF ONE COMPONENT

Limit: 140 g/l COV (2007); 140 g/l COV (2010)  
This product contains 16,05 g/l COV max.

## USES

Tile joints independent to their absorption or format.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

## FEATURES

- Excellent adhesion.
- Available in white, clay beige, pearl grey and black colour.
- Easy to apply.
- Do not use for swimming pools.
- Unsuitable for exposure to water
- Storage: 12 months inside its original packing and kept free from damp and humidity.

## IDEAL FOR

- Meeting joints of tiles and skirting independent to their grade of absorption and format

Clay colour



White colour



Beige colour



Pearl grey colour



Black colour



Pallet of 120 cases  
of 12 x 200 g



## Preparation

Ready to use



## Performance

1,06 m<sup>2</sup>/kg



7.0 - 8.0



## Maximum thickness per layer

1 mm.



## Maximum granulometry

200 microns



## Fire classification

A2 - s1 - d0



## Useful life

Unlimited



## Drying time in 1mm thickness

Cement and paint: 4 - 5 hrs



## Adherence

> 8 kg/cm<sup>2</sup> on concrete