

B-24

DIY

Brico



TILE GROUT

Product designed to fill, restore, waterproof and seal tile joints up to 1 mm.



INTERIOR



SURFACES

Tile joints regardless of absorption and format.

Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

CHARACTERISTICS

- Excellent adhesion.
- Available in white.
- Easy to apply.
- Not suitable for swimming pools.
- Not suitable for continued submersion.
- Storage: 12 months in its original packaging and protected from moisture.

IDEAL FOR

- Tile and skirting board grouting regardless of the degree of absorption and format.

INFORMATION ABOUT DIRECTIVE 2004/42/CE

CATEGORY I1, HIGH PERFORMANCE COMPONENT COATINGS, WATERBASED

Limit: 140 g/l VOC (2007); 140 g/l VOC (2010)

This product contains max: 16,05 g/l VOC



200g

Pallet of 120 boxes
of 12 x 200 g



Preparation
Ready to use



Performance
1,06 m²/kg



pH 7.0 - 8.0



Maximum thickness per layer
1 mm



Maximum granulometry
200 microns



Fire classification
A2 - s1 - d0



Use time
No limits



Drying in 1 mm thickness
Cement and paint: 4 - 5 H



Adherence
>8 kg/cm² on concrete



BAIXENS ESPAÑA
POL. IND. MONCARRA, S/N
46230 ALGINET (VALENCIA)
T.: 961.750.834
F.: 961.752.471

BAIXENS FRANCE
14, RUE DU PONT NEUF
75001 PARIS (FRANCE)
T.: 0.800.90.14.37
F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA
VIA PIETRO NENNI, 36
46019 CICOGNARA - MANTOVA (ITALY)
T.: 0375/88181/790016 F.: 0375/88831
www.bulova-pennelli.com

BAIXENS PORTUGAL / ARGATINTAS
AVENIDA PORTAS DO MINHO, Nº 711
4760 - 706 RIBEIRÃO,
V.N. FAMALICÃO
T.: 252 910 030 | www.argatintas.pt

B24NF1731A20 / B24NF1673A20 / B24NF2653A20 / B24NF1554A20 / B24NF1555A20

Commercial sheet that cancels and replaces any previous version. 06/2022. The technical data have been obtained on standardised surfaces and under laboratory conditions, so they can vary according to the conditions of use. These technical data do not imply any guarantee on our part in the event of improper use of our product.