


B-32



EXPANSION JOINT SEALER

Product designed for sealing expansion joints or dynamic joints.



INFORMATION ABOUT DIRECTIVE 2004/42/CE

CATEGORY I1, HIGH PERFORMANCE COMPONENT COATINGS, WATERBASED

Limit: 140 g/l VOC (2007); 140 g/l VOC (2010)

This product contains max: 2,91 g/l VOC

SURFACES

Terrace and façade expansion joints. All kinds of joints.
Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

CHARACTERISTICS

- Easy to apply.
- Excellent rheology for use as a joint sealant.
- Great elongation power.
- Waterproof.
- Semi-transparent product once dried.
- Storage: 12 months in its original packaging and protected from moisture.



IDEAL FOR

- Sealing expansion and/or dynamic joints.



Pallet of 120 boxes
of 12 x 310 ml



Preparation
Ready to use



**Performance in a 5mm thick layer
and 1cm in width**
57 - 61 g/lineal metre



9.0 - 10.0



Maximum thickness per layer
5 mm



Elongation before breakage
>300 %



Fire classification
E - d0



Use time
No limits



Drying in 1 mm thickness
6 - 7 H



Maximum granulometry
200 microns



BAIXENS ESPAÑA
POL. IND. MONCARRA, S/N
46230 ALGINET (VALENCIA)
T.: 961.750.834
F.: 961.752.471

BAIXENS FRANCE
14, RUE DU PONT NEUF
75001 PARIS (FRANCE)
T.: 0.800.90.14.37
F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA
VIA PIETRO NENNI, 36
46019 CICOGNARA - MANTOVA (ITALY)
T.: 0375/88181/790016 F.: 0375/88831
www.bulova-pennelli.com

BAIXENS PORTUGAL / ARGATINTAS
AVENIDA PORTAS DO MINHO, Nº 711
4760 - 706 RIBEIRÃO,
V.N. FAMILICÃO
T.: 252 910 030 | www.argatintas.pt

B32NF1310A20