


B-33



OUTDOOR CRACK FILLER

Textured product designed for filling and sealing microcracks, cracks and dynamic cracks.



INFORMATION ABOUT DIRECTIVE 2004/42/CE

CATEGORY 11, HIGH PERFORMANCE COMPONENT COATINGS, WATERBASED

Limit: 140 g/l VOC (2007); 140 g/l VOC (2010)

This product contains max: 26,87 g/l VOC

SURFACES

Plaster, plaster of Paris, cement, brick, stone, wood, concrete, aerated concrete, semi-absorbent surfaces.

Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

CHARACTERISTICS

- Microfibred.
- Textured.
- Excellent thixotropy.
- Minimal weakening.
- High adherence.
- Smoothing without migration of fibre to the surface.
- Storage: 12 months in its original packaging and protected from moisture.



IDEAL FOR

- Filling and sealing microcracks, cracks and dynamic cracks.



Pallet of 120 boxes of 12 x 310 ml



Preparation
Ready to use



Performance in a 5mm thick layer and 1cm in width
36 - 48 g/lineal metre



pH 9.0 - 10.0



Maximum thickness per layer
10 mm



Adherence
> 11 Kg/cm² on concrete



Fire classification
D - s2 - d0



Use time
No limits



Drying in 1 mm thickness
6 - 7 H



Maximum granulometry
1000 microns without fibre



BAIXENS ESPAÑA
POL. IND. MONCARRA, S/N
46230 ALGINET (VALENCIA)
T.: 961.750.834
F.: 961.752.471

BAIXENS FRANCE
14, RUE DU PONT NEUF
75001 PARIS (FRANCE)
T.: 0.800.90.14.37
F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA
VIA PIETRO NENNI, 36
46019 CICOGNARA - MANTOVA (ITALY)
T.: 0375/88181/790016 F.: 0375/88831
www.bulova-pennelli.com

BAIXENS PORTUGAL / ARGATINTAS
AVENIDA PORTAS DO MINHO, Nº 711
4760 - 706 RIBEIRÃO,
V.N. FAMILICÃO
T.: 252 910 030 | www.argatintas.pt