


# B-35



## PLASTIC FIBRE PASTE

Product designed to repair microfissures and stubborn cracks.



### SURFACES

Plaster, plaster of Paris, cement, brick, stone, wood, concrete, aerated concrete, semi-absorbent surfaces.

Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

### CHARACTERISTICS

- Reinforced with fibreglass.
- Extra white.
- Applicable in thick layers.
- Excellent thixotropy.
- Highly flexible.
- High adherence.
- Storage: 12 months in its original packaging and protected from moisture.

### IDEAL FOR


- Covering and repairing static and dynamic cracks.
- Filling small holes.
- Replacing fibreglass bands.

#### INFORMATION ABOUT DIRECTIVE 2004/42/CE

CATEGORY 11, HIGH PERFORMANCE COMPONENT COATINGS, WATERBASED

Limit: 140 g/l VOC (2007); 140 g/l VOC (2010)

This product contains max: 44,87 g/l VOC



Pallet of 120 boxes of 12 x 310 ml



**Preparation**  
Ready to use



**Performance in a 5mm thick layer and 1cm in width**  
50 - 60 g/lineal metre



9.0 - 10.0



**Maximum thickness per layer**  
10 mm



**Adherence**  
> 14 Kg/cm<sup>2</sup> on concrete



**Fire classification**  
D - s2 - d0



**Use time**  
No limits



**Drying in 1 mm thickness**  
6 - 7 H



**Maximum granulometry**  
10 microns without fibre



**BAIXENS ESPAÑA**  
POL. IND. MONCARRA, S/N  
46230 ALGINET (VALENCIA)  
T.: 961.750.834  
F.: 961.752.471

**BAIXENS FRANCE**  
14, RUE DU PONT NEUF  
75001 PARIS (FRANCE)  
T.: 0.800.90.14.37  
F.: 0.800.90.20.52

**BAIXENS ITALIA / BULOVA**  
VIA PIETRO NENNI, 36  
46019 CICOGNARA - MANTOVA (ITALY)  
T.: 0375/88181/790016 F.: 0375/88831  
www.bulova-pennelli.com

**BAIXENS PORTUGAL / ARGATINTAS**  
AVENIDA PORTAS DO MINHO, Nº 711  
4760 - 706 RIBEIRÃO,  
V.N. FAMILICÃO  
T.: 252 910 030 | www.argatintas.pt

B35NF1316A20