

B-36

BRICO®

COVER-DRIBBLE PUTTY

Product suitable for covering synthetic stucco and renovating rugged or embossed surfaces.



INDOOR



CLASSIFICATION ACCORDING TO
REGULATION EN 16566
G3S2V3W2A0C0R0

USES

Gypsum, plaster, plasterboard boards, cement, stippled paint, non-elastic synthetic paint. Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Easy to apply, smooth and sand.
- Fast setting.
- Smooth and fine finish.
- Non-repellent.
- Good covering power.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Renovating and levelling of substrates.
- Smoothing of walls with flaws (scratches, lines, dents).



Pallet of 66
sacks of 15 Kg



Pallet of 35 cases
of 4 x 5 Kg



Water for mixing

0,43-0,45 litres of water per Kg. of powder



Performance

0,60 m²/kg



5,5 - 6,5



Maximum thickness for applying

4 mm. for plastering
Unlimited for filling



Adherence

> 8 Kg/cm² on cement and paint



Fire classification

A1



Useful life

1 hr.30' - 2 hrs



Drying time in 1mm thickness

Concrete and paint: 6 - 7 hrs.
Plaster: 2 - 3 hrs



Maximum granulometry

300 microns