

B-37

BRICO®

ANTI-HUMIDITY BARRIER

Waterproofing in powder for treating anti-humidity.



COATED

BY ALL TYPES OF NON-ELASTIC PAINTS ONCE COMPLETELY DRY

USES

Gypsum bases, plaster, cement, stone, concrete, etc.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Standard setting.
- Easy to apply.
- Anti-humidity barrier and protection.
- Permeable to water vapour.
- Waterproof to liquid water.
- Applicable with a brush (as paint) or using trowel or spatula (as plastering).
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Sealing, covering and protecting any type of substrate exposed to the aggressiveness of water and humidity, in the interior or exterior such as basements, interred foundations, swimming pools, garden areas, etc.



Pallet of 35 cases
of 4 x 5 Kg



Pallet of 42 cases
of 12 x 1 Kg



Water for mixing

0,40 litres of water per Kg. of powder.(paint consistency)
0,30 litres of water per Kg. of powder.(plaster consistency)



Performance

1 - 1,5 Kg/m²



12.0 - 13.0



Maximum thickness per layer

10 mm. for plastering
3 mm. as paint application



Adherence

> 7 Kg/cm² on cement



Fire classification

A1



Useful life

3 - 4 hrs.



Drying time in 1mm thickness

Concrete: 3 - 4 hrs.
Plaster: 2 - 3 hrs.



Maximum granulometry

900 microns