

CX-36

Preparation of surfaces

LATEXPLAST

Plastic latex for varnishing, sealing, reinforcing and protecting interior surfaces.



* information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions).



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY g1, WATER-BASED PRIMERS

Limit: 50 g/l VOC (2007); 30 g/l VOC (2010)
This product contains < 30 g/l VOC max.

SURFACES

Stone, concrete, cement, plaster, gypsum, semi-absorbent surfaces, common building surfaces.

Surfaces must be sound, dry, cohesive, absorbent, well-adhered, clean and free of dust.

CHARACTERISTICS

- Good compatibility with cement, plaster and lime.
- Transparent when dry.
- Reinforcement of tempera paints.
- Sealer on gypsum, mortar, concrete or stucco surfaces.
- Easy to apply.
- Quick drying.
- An elastic, flexible product.
- Suitable for domestic use.

IDEAL FOR

- Using as a final protective varnish on decorative finishes, watercolours, canvases, etc.
- Using as a primer to treat porous interior surfaces prior to the application of paints.
- Glueing of sharp joints and paper corners.

ON-SITE APPLICATION

SURFACE PREPARATION

The surface must be sound, clean and free of any trace of saltpetre, fungi, microorganisms, grease, release oils and, in general, any type of material that could make it difficult for the product to adhere to the surface.



CX-36

Preparation of surfaces

LATEXPLAST

ON-SITE APPLICATION

CLEANING

When the supports present traces of fungi, algae or other types of microorganisms, we will proceed with the curative treatment, first of all, with a quick mold cleaner. This will be applied to the surface to be treated and after 5 -10 minutes of action, the support will be cleaned with the help of a pressurized water machine or with a hard bristle brush. Next, and once the support is completely dry, a broad-spectrum biocide cleaner will be applied until the support is completely impregnated. This treatment is called preventive, it is very effective and serves to prevent the future appearance of microorganisms.

If there are saltpetre stains on the surface to be treated, carry out an initial cleaning process with our **RX-523 CLEAN SAL**, applying the material and then scraping it with a hard bristle brush. After mechanically cleaning the surface, it will need to be rinsed with plenty of clean water in order to neutralise any **CLEAN SAL** residue that may remain on the surface.

Any grease or oil must be completely eliminated to allow the product to adhere correctly to the surface. Therefore, we recommend using **RX-527 CLEAN OIL** for correct and total elimination of these substances.

DIRECTIONS FOR USE

A ready-to-use product.

As a primer, **CX-36** can be used pure or diluted with 2 to 3 times its weight in water (for each litre of product, 2 to 3 litres of clean, drinkable water can be added), depending on the desired effect.

It may be applied with a brush and/or roller.

TECHNICAL CHARACTERISTICS

Density	0,99 ± 0.07 g/ml
Fire classification	E - d0
pH	7.0 – 8.0
Brookfield Viscosity	14000 - 22000 cP. (A/4/10)
Cleaning of tools	With water

Drying time for 1 mm layer on painted surface (*)	1 H - 1 H 15'
Nature	Water-based product

(*) The ambient temperature, the relative humidity of the air and the absorption of the surface influence the drying time.

CX-36

Preparation of surfaces

LATEXPLAST

TECHNICAL CHARACTERISTICS

THEORETICAL PERFORMANCE (**)		INFORMATION ON DIRECTIVE 2004/42/CE – CATEGORY g1	
litre applied per m ²	0,250 - 0,300	LIMIT COV	CONTENT COV
		50 g/l (2007) – 30 g/l (2010)	< 30 g/l maximum

(**) The practical performance depends on the surface (type, condition and absorption), the method of application and the degree of dilution.

INFORMATION OF INTEREST

The manufacturing process is controlled in batches, which allows traceability of any incident. The quality system used includes each article's design and production controls, both in terms of the raw materials used, guaranteeing uniform manufacturing, and the final item obtained. The use of ecotechnologies in our facilities' manufacturing processes allows for efficient work, without damaging the environment that surrounds us.

- Non-flammable product.
- Avoid the product coming into contact with skin and eyes.
- Smoking, eating and drinking must be prohibited in the application area.
- Comply with legislation on health and safety at work.
- Keep the product in a dry place, in original containers that are kept properly closed.
- Store the containers between 5°C and 35°C.
- Recommended storage time: 12 months from the date of manufacture in its original packaging and protected from moisture.

For further information on protective measures and first aid, please refer to the product's Safety Data Sheet.

OBSERVATIONS

- The reading of this product's data sheet is indispensable for the correct use and application.
- The principles given in this data sheet have been obtained under normal laboratory conditions and on normal surfaces, results may vary, depending on the conditions of construction, (absorption of the surface, thickness applied, mixing water, temperature and humidity). The intervals exhibited have been obtained by means of historical measures. Slight high or low deviations to ranges presented in this technical data sheet will be admitted according to internal technical criteria and do not cause decrease in quality or will it affect the final performance of the product, being due, amongst other factors, to variations in the conditions of measure or uncertainty associated with the instruments used.
- The working conditions of users are beyond our control.
- The product must not be used for purposes other than those specified. It is recommended that the instructions for use be strictly followed.
- It is essential that the status of the surfaces be assessed prior to each application.
- Ideal temperature for applying from 5°C to 35°C.

CX-36

Preparation of surfaces

LATEXPLAST

OBSERVATIONS

- Do not mix with any material, as it will not retain its technical characteristics.
- Do not apply to wet surfaces.
- Do not apply to painted surfaces.
- Do not apply to crystalline or blocked surfaces.
- The technical department of **ESTABLECIMIENTOS BAIXENS** hereby informs you that the designs of recently launched new products are considered to be in an experimental phase until an annual history can be constituted. From then on, the newly designed product is considered to be fully consolidated in the market. In the meantime, **BAIXENS** reserves the right to adapt its variable specifications or working ranges according to technical criteria. Any details subject to modification will be identified with an asterisk for easy identification; these may be recently created products and/or products in an experimental phase or improvements in our various ranges due to market needs and/or demands.
- We have a technical-commercial team at your disposal that can advise you with regard to any doubts or queries.

PACKAGING

FORMAT	4 l.	750 ml.
UNIT/BOX	4	12
PALLETS	24 boxes	44 boxes



Internal code CX36NF1782A20


BAIXENS
 baixens.com

*Testing the
 difference*
BAIXENS ESPAÑA
 POL. IND. MONCARRA, S/N
 46230 ALGINET (VALENCIA)
 T.: 961.750.834
 F.: 961.752.471

BAIXENS FRANCE
 14, RUE DU PONT NEUF
 75001 PARIS (FRANCE)
 T.: 0.800.90.14.37
 F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA
 VIA PIETRO NENNI, 36
 46019 CICOGNARA - MANTOVA (ITALY)
 T.: 0375/88181790016 F.: 0375/88831
 www.bulova-pennelli.com

BAIXENS PORTUGAL / ARGATINTAS
 AVENIDA PORTAS DO MINHO, Nº 711
 4760 - 706 RIBEIRÃO,
 V.N. FAMILIÇÃO
 T.: 252 910 030
 www.argatintas.pt