

E-03

Enlucite<sup>®</sup>

## FINISHES

Specially indicated for concealing and smoothing small flaws



INTERIOR



### USES

Gypsum, plaster, cement, non-elastic plastic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

### FEATURES & USES

- Slow setting
- Easy to apply, smooth and sand.
- Does not tear away when worked with iron.
- Thin layer applicable.
- Fills in small flaws in wood.
- Ideal for concealing small fissures and micro-fissures.
- Conceals non-movement cracks and non-structural character.
- Storage: 12 months inside its original packing and kept free from damp and humidity.



### RECOAT

BY ALL TYPES OF NON-ELASTIC PAINTS ONCE COMPLETELY DRY CODE (EN 16566):

CÓDIGO (EN 16566):

**G3S2V3W2A0C0R0**



Pallet of 66 sacks  
of 15 kg.



Pallet of 35 cases  
of 4 x 5 kg.



Pallet of 36 cases  
of 20 x 1 kg.



#### Water for mixing

0,45 – 0,50 litres of water per kg of plaster



#### Performance in 1mm layer

1.61 - 1.76 Kg/m<sup>2</sup>



6.0 - 7.0



#### Maximum thickness per layer

1 mm



#### Adhesion

> 7 Kg/cm<sup>2</sup> on cement and paint



#### Fire classification

A2 - s1 - d0



#### Useful life

8 H Aprox.



#### Drying in 1mm thickness

Plaster & paint: 4 – 6 hrs  
Concrete: 3 hrs. approx.



#### Maximum granulometry

150 microns