

E-10

Enlucite®

# UNIVERSAL

Especially suitable for smoothing cement substrates



**RECOAT**  
BY ALL TYPES OF NON-ELASTIC PAINTS  
ONCE COMPLETELY DRY

CODE (EN 16566):

**G3S3V3W1A0C0R0**

## USES

Gypsum, plaster, cement, concrete, brick walls, stone, synthetic paint, tiles, molten glass, low absorbent bases.  
Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

## FEATURES & USES

- Fast setting.
- Quick dry.
- Applicable in thin and thick layer.
- Easy to apply.
- Strong adhesion.
- Very strong finish.
- Protective coating.
- Full plastering of façades.
- Covering non-structural gaps and cavities on façades.
- Storage: 6 months inside its original packing and kept free from damp and humidity.
- The direct use of paint containing alkali resistant pigments can produce discolouration. In order to avoid this cosmetic damage, we recommend prior to painting, the use of dissolvent or water-based penetrating fixer consolidator or an acrylic absorption regulated primer. For more information on precautions to bear in mind before applying paints on cement or exterior substrates please consult our information brochure.



Pallet of 66 sacks  
of 15 kg.



Pallet of 35 cases  
of 4 x 5 kg.



### Water for mixing

0,35 – 0,40 litres of water per kg of plaster



### Performance in 1mm layer

1.54 - 1.64 Kg/m<sup>2</sup>/mm



10.0 - 11.0



### Maximum thickness per layer

10mm. for plastering  
Unlimited for filling in



### Adhesion

> 15 Kg/cm<sup>2</sup> on cement.



### Fire classification

A2 - s1 - d0



### Useful life

20 – 40 mins.



### Drying in 1mm thickness

Concrete: 3- 4 hrs.



### Maximum granulometry

300 microns