

E-11

Enlucite®

PLASTIC STUCCO

Structured renovating plaster for manual or mechanical application.



INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY II, HIGH PERFORMANCE ONE COMPONENT
WATER-BASED COATINGS

LIMIT: 140G/L COV (2007); 140g/l COV(2010)
This product contains 1,42g/l COV max.

RECOAT

BY ALL TYPES OF NON-ELASTIC PAINTS ONCE
COMPLETELY DRY

CODE (EN 16566):

G3S1V2W2A0C0R0

INTERIOR



USES


Gypsum, plaster, cement, synthetic paint, laminated stipple paint and fibre-glass fabric. Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.


FEATURES & USES

- Excellent workability. Easy to smooth and sand.
- Non-drip.
- Does not mount or roll on the joints/splice.
- Great covering power.
- Smoothing of embossed bases.
- Renovation of old bases, repairing of stripes, dents or micro-fissures.
- Covering of pores in wood.
- Creating of embossed jobs for decoration.
- Storage: 12 months inside its original packing and kept free from damp and humidity.





25Kg	Pallet of 33 buckets of 25 kg.	5Kg	Pallet of 30 cases of 4 x 5 kg.
1Kg	Pallet of 44 cases of 12 x 1 kg.	400g	Pallet of 45 cases of 18 x 400 g.


 **Preparation**
Ready to use.
Clean tools with water.

 **Rendimiento**
1.75 - 1.85 Kg/m²/mm

 **pH**
9.0 - 10.0

 **Maximum thickness per layer**
2mm.

 **Adherencia**
> 7 Kg/cm² sobre cemento y pintura

 **Clasificación al fuego**
A2 - s1 - d0

 **Useful life**
Unlimited

 **Secado en 1 mm de espesor**
Cemento y pintura: 12 H aprox.

 **Granulometry**
50 microns