

E-13

Enlucite[®]

ELASTIC WITH FIBRE

Water-based acrylic putty special for treating cracks and rebellious fissures



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY I, HIGH PERFORMANCE ONE COMPONENT WATER-BASED COATINGS

LIMIT: 140G/L COV (2007); 140g/l COV(2010)
This product contains 45,09g/l COV max.

RECOAT

BY ALL TYPES OF NON-ELASTIC PAINTS ONCE COMPLETELY DRY

CODE (EN 16566):

G3S2V2W2A0C0R0



USES

Gypsum, plaster, cement, brick, stone, wood, concrete, aerated concrete, semi-absorbent substrates.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES & USES

- Equipped with fibre-glass.
- Applicable in thickness.
- Excellent thixotropy.
- Highly flexible.
- Strong adhesion.
- Substitutes fibre-glass bands.
- Storage: 12 months inside its original packing and kept free from damp and humidity.



15Kg Pallet of 33 buckets of 15 kg.

5Kg Pallet of 24 cases of 4 x 5 kg.

1Kg Pallet of 24 cases of 18 x 1 kg.

Preparation
Ready to use.
Clean tools with water.

Performance in 1cm fissures
75 - 85 g/m lineal

pH 9.0 - 10.0

Maximum thickness per layer
10 mm

MPa Adhesion
> 14 Kg/cm² on concrete

Fire classification
D - s2 - d0

Useful life
Unlimited

Drying in 1mm thickness
12 hrs

Granulometry
10 microns with no fibre threads