

RG-115

Unijunta®

REINFORCEMENT TAPE

Paper tape for laminated plasterboard sheets (pyl) and fibro-plaster (pyf). Shredded, Microperforated and pre-folded.



RG-115A

| | |
|--|--|
| Length | 30m. |
| Width | 50mm. |
| Dimensional stability | Length: 0,1% |
| | Width: 1,2% |
| Corrosion resistance | 48 hours in salt spray chamber (in accordance To NF EN ISO 9227 Regulation). |
| Paper tensile strength | 5,239 N/mm |
| Strap tensile strength | 690 N/mm ² |
| Reaction to fire | Same as the plate with which it is used |
| Operational Temperature | Between 5°C to 30°C |
| CE Branded according to Regulation NF EN 14353 | |

Paper tape for reinforcing corners on laminated plasterboard sheets (pyl) and fibro-plaster (pyf) with 2 flexible metal anti-corrosion treated straps.



5 cm x 30m Roll:
Pallet of 50 cases of 10 units.

RG-115B

| | |
|---|--|
| Length | 150m. |
| Width | 50mm. |
| Dimensional stability | Length: 0,1% |
| | Width: 1,2% |
| Loading resistance | PND |
| Tensile strength | 5,239 N/mm. |
| Reaction to fire | Same as the plate with which it is used. |
| Operational Temperature | Between 5°C to 30°C |
| CE Branded according to Regulation EN 13963 | |

Paper tape for laminated plasterboard sheets (pyl) and fibro-plaster (pyf). Shredded, Microperforated and pre-folded.



5 cm x 150m Roll:
Pallet of 50 cases of 10 units.