


RX-303

Rualaix®

RUSTIC PLASTER IN PASTE

Decorative plaster suitable for obtaining rustic looking walls.



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A + (very low emissions).

INDOOR



RECOATING

CBY RX-502 CERALAIX FINISHING WAX

INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY I, HIGH PERFORMANCE ONE COMPONENT COATINGS, WATER-BASED

LIMIT: 140g/L COV (2007); 140g/l COV(2010)

This product contains 0,15g/l COV max.

CLASSIFICATION ACCORDING TO REGULATION
EN 16566

G3S1V2W2A0C0R0

USE

Gypsum, plaster, cement, non-elastic synthetic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Does not need sanding.
- Easy to apply in one step.
- Smooth touch finishes.
- Absence of splice.
- Possibility of covering gaps and small holes.
- Possibility of retouching shapes created before the surface is dry.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Obtaining rustic finished walls, old-fashioned and imitation mud walls.



20kg Pallet of 33 containers x 20 Kgs.

5Kg Pallet of 120 containers of 5 Kgs.



PREPARATION

Ready to use.
Clean tools with water.



PERFORMANCE

1.50-1.60 Kg/m²/mm



7.0 – 8.0



MAXIMUM THICKNESS PER COAT

2 mm



ADHESION

>13kg/cm² on cement.
>17kg/cm² on paint.



FIRE RESISTANCE CLASSIFICATION

A2- s1-d0



USEFUL LIFE

Unlimited



DRYING TIME IN 1mm THICKNESS

Concrete and paint: 5 – 6 hrs.



MAXIMUM GRANULOMETRY/GRADING

200 microns