

RX-530

ISOLXTREM®

FIXATHERM

Acrylic fixative with thermo-insulating, sound-absorbing and anti-condensation properties.



INFORMATION ON DIRECTIVE 2004/42/EC

CATEGORY g1, WATERBASED PRIMERS

Limit: 50 g/l VOC (2007); 30 g/l VOC (2010)
This product contains max. 1,98 g/l VOC.

SURFACES

RX-127 Rualaix Isolxtrem Interiors, plaster, laminated plasterboard, gypsum, cement, concrete and absorbent masonry surfaces.

Surfaces must be sound, dry, cohesive, absorbent, well-adhered, clean and free of dust.

CHARACTERISTICS

- A fixing and insulation product.
- Contains microspheres.
- A water-based product.
- Complements the Isolxtrem System.
- Confers thermo-insulating, sound-absorbing and anti-condensation properties.
- Insulating barrier in synergy with Isolxtrem System components.

IDEAL FOR

- Fixing surfaces prior to the application of RX-417 Pintherm.
- Fixing surfaces treated with RX-127, improving its effectiveness.

ON-SITE APPLICATION

SURFACE PREPARATION

The surface must be sound, clean and free of any trace of saltpetre, fungi, microorganisms, grease, release oils and, in general, any type of material that could make it difficult for the product to adhere to the surface.

Clean and scrape off all loose or poorly adhering parts.



RX-530

ISOLXTREM®

FIXATHERM

ON-SITE APPLICATION

CLEANING

If surfaces present traces of fungi, algae or other type of microorganisms, we first proceed to curative treatment with our **RX-524 CLEAN MICRO**. Apply the product to the surface to be treated. After 5-10 minutes of action, clean the surface using a pressurised water machine or with a hard bristle brush. Then, once the surface is completely dry, **RX-524 CLEAN MICRO** should be applied until the surface is completely impregnated. This preventive treatment is very effective and prevents future presence of microorganisms.

If there are saltpetre stains on the surface to be treated, carry out an initial cleaning process with our **RX-523 CLEAN SAL**, applying the material and then scraping it with a hard bristle brush. After mechanically cleaning the surface, it will need to be rinsed with plenty of clean water in order to neutralise any **CLEAN SAL** residue that may remain on the surface.

Any grease or oil must be completely eliminated to allow the product to adhere correctly to the surface. Therefore, we recommend using **RX-527 CLEAN OIL** for correct and total elimination of these substances.

If the supports present cavities, they must be scraped and eliminated until reaching the consistent bottom. The consistent support is the one usually formed by brick, or cement, as long as it can support the weight and tension of the subsequent layers applied, without disintegrating or altering its structure.

DIRECTIONS FOR USE

Shake the product before use.

Apply by brush, roller or airless paint gun.

For the first coat of the product to penetrate the surface, it must be diluted 5% with clean drinking water. It is advisable to apply a second, undiluted coat of the product.

To achieve total efficiency, we recommend applying **RX-530 FIXATHERM** on insulating panels or on plaster from the ISOLXTREM range, in the quantity indicated and then, as a final finish, applying **RX-417 PINTHERM**.

Allow 24 hours before applying **RX-417 PINTHERM**.

TECHNICAL CHARACTERISTICS

Relative density	0.80 ± 0.07 g/l	Deep drying time on absorbent surfaces	30 mins when applied in a thin layer on plaster surfaces
Reaction to fire	E - d0	Tool cleaning	With water
pH	9.0 - 10.0	Brookfield viscosity	11000 - 17000 (A/4/10)
Yield	250 ml/m ²	Information on Directive 2004/42/EC - Category g1	50 g/l (2007) - 30 g/l (2010).COV content 1.98 g/l maximum
Solids	30 - 35 %	Thermal conductivity (ASTM D 5334-08)	0.343 W/m.k

RX-530

ISOLXTREM®**FIXATHERM**

INFORMATION OF INTEREST

The manufacturing process is controlled in batches, which allows traceability in the case of any incident. The quality control system used includes, the individual design and development of each article, both with the raw materials used confirming manufacturing uniformity, as well as the final product obtained. The use in our facilities of eco-technology in the manufacturing process allows the completion of environmentally friendly efficient work.

- Non-flammable product. Irritant.
- Avoid contact with eyes and skin.
- Smoking, eating or drinking in the area of use is prohibited.
- Comply with Health and Safety at Work Executive regulations.
- Store the product in a dry place, in its original packaging firmly closed and free from humidity.
- Store the containers between 5°C and 35°C.
- Recommended storage time: 12 months as from date of manufacture, closed in its original packing and away from humidity.

Further information relative to protection measures and first aid, check Product Safety Sheet.

OBSERVATIONS

- The reading of this product's data sheet is indispensable for the correct use and application.
- The data provided in this data sheet are for guidance only and should not be considered binding. The data has been obtained in normal laboratory conditions and on standardised surfaces, and can vary depending on the conditions in which they are applied (absorption of the surface, applied thickness, temperature, environmental humidity, etc.). The intervals displayed have been shaped by measurement history. Slight deviations from the ranges presented in this technical sheet, whether higher or lower, will be accepted according to internal technical criteria and will not result in a loss of quality or affect the performance of the final product, due, among other factors, to variations in measurement conditions and the uncertainty associated with the instruments used.
- Work conditions of the user are out of our control.
- The product should not be utilized for other uses except the ones indicated. It is advisable to follow strictly the recommendations of use given.
- A previous inspection of the state of the surface before use is fundamental.
- Do not mix the product with any material, as it will not retain its technical characteristics.
- It will lose its technical features if mixed with any other material.

RX-530

ISOLXTREM®

FIXATHERM

OBSERVATIONS

- Do not wet the surfaces before applying.
- Do not apply on non-absorbent surfaces.
- Do not apply the product under unfavourable environmental conditions (e.g. strong winds, or where there are risks of rain or frost). If applied, use covers or application curtains.
- **ESTABLECIMIENTOS BAIXENS'** technical department informs that the new designs in the development of recent launches are considered in their experimental phase until an annual revision is made. From this point on, the product of a recent launch is considered as being totally consolidated in the market. In the meantime, **ESTABLECIMIENTOS BAIXENS** reserves its right to adapt the variable specifications or ranges of work, according to technical criteria. The information subject to modification, will be identified with an asterisk at the top for easy recognition of those products which are the subject of new creation or are subject to an experimental phase or improvement in our different ranges because of market demand and or needs.
- We have a technical-sales team at your disposal for technical advice or consultation.

PACKAGING

FORMAT	4 l.	750 ml.
UNITS/BOX	-	12
PALLETS	120 CANS	44 BOX



Internal code RX530NF2043A20


BAIXENS
 baixens.com

*Testing the
 difference*
BAIXENS ESPAÑA
 POL. IND. MONCARRA, S/N
 46230 ALGINET (VALENCIA)
 T.: 961.750.834
 F.: 961.752.471

BAIXENS FRANCE
 14, RUE DU PONT NEUF
 75001 PARIS (FRANCE)
 T.: 0.800.90.14.37
 F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA
 VIA PIETRO NENNI, 36
 46019 CICOGNARA - MANTOVA (ITALY)
 T.: 0375/88181/790016 F.: 0375/88831
 www.bulova-pennelli.com

BAIXENS PORTUGAL / ARGATINTAS
 AVENIDA PORTAS DO MINHO, Nº 711
 4760 - 706 RIBEIRÃO,
 V.N. FAMALICÃO
 T.: 252 910 030
 www.argatintas.pt