

RX-804

Unijunta®

FIXAPLAC

Adhesion putty suitable for placing plasterboard sheets.
Medium setting.



INTERIOR

**COATED**

BY ALL TYPES OF NON-ELASTIC PAINTS
ONCE COMPLETELY DRY

USES

Cement, gypsum, plaster, pre-fabs.
Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Easy to knead.
- Excellent adhesion.
- Standard setting.
- Easy to apply.
- Storage: 6 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Fixing and pasting plasterboard sheets on constructed walls.



Pallet of 66
sacks of 15 Kg.



Pallet of 35
cases of 4 x 5 Kg.

**Water for mixing**

0,45 - 0,48 litres of water per Kg of powder.

**Performance**

2 – 3 Kg/m²/mm



7.0 - 8.0

**Maximum thickness per layer**

15 mm

**Adhesion**

> 10 Kg/cm² on concrete

**Fire Classification**

A1

**Useful life**

1 H 15' - 2 H 15'

**Drying Time in 1 mm thickness**

Plaster: 1 H 30' - 2 H

**Maximum Granulometry**

300 microns